



24-Port Layer 3 Managed Gigabit Switch with 4 Gigabit SFP Slots

Model: **GS 5024S4**



Features

- Support IEEE 802.1d, IEEE 802.1w, IEEE 802.1s, IEEE 802.1p, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3ae standards ;
- L3 management, support DHCP Server, QoS, ACL, SNMP V1/V2/V3, IGMP Snooping v1/v2;
- Support STP/RSTP/MSTP (ERPS), Support loop detection and self-healing, support remote loopback monitoring and control (802.3ah OAM); Support IPV4/IPV6,RIP,OSPF
- Support multiple VLAN division, MAC VLAN, Protocol VLAN, Private VLAN;
- Support IP address + MAC address + VLAN+Port binding, DHCP Snooping, support IP source and DAI protection;

Technical parameters

Model	GS5024S4
AC INPUT	AC INPUT (100-240V)
Ethernet Port	24 * 10/100/1000Mbps RJ45 Port 4 * 10G SFP+ Port 1 * RJ45 Console Port 1 * USB Port
Bandwidth	128Gbps
Packet Forwarding rate	95.23Mpps
DDR SDRAM	128MB
Flash Memory	16MB
Packet Buffer Memory	12Mbit
MAC Address	16K
Jumbo frame	12Kbytes
VLANs	4096



Standard

Network Protocols	IEEE 802.3: Ethernet MAC Protocol
	IEEE 802.3i: 10BASE-T Ethernet
	IEEE 802.3u: 100BASE-TX Fast Ethernet
	IEEE 802.3ab: 1000BASE-T Gigabit Ethernet
	IEEE 802.3z: 1000BASE-X Gigabit Ethernet (optical fiber)
	IEEE 802.3ae: 10G Ethernet (optical fiber)
	IEEE 802.3az: Energy Efficient Ethernet
	IEEE 802.3ad: Standard method for performing link aggregation
	IEEE 802.3x: Flow control
	IEEE 802.1ab: LLDP/LLDP-MED (Link Layer Discovery Protocol)
	IEEE 802.1p: LAN Layer QoS/CoS Protocol Traffic Prioritization (Multicast filtering function)
	IEEE 802.1q: VLAN Bridge Operation
	IEEE 802.1x: Client/Server Access Control and Authentication Protocol
	IEEE 802.1d: STP
	IEEE 802.1s: MSTP
IEEE 802.1w: RSTP	

Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A
	EMS: EN61000-4-2 (ESD), EN61000-4-4 (EFT), EN61000-4-5 (Surge)
Network Media	10BASE-T: Cat3、 4、 5 or above UTP(≤100 M)
	100BASE-TX: Cat5 or above UTP(≤100 M)
	1000BASE-TX: Cat5 or above UTP(≤100 M)
	Multi-mode Fiber: 50/125、 62.5/125、 100/140um
	Single-mode Fiber: 8/125、 8.7/125、 9/125、 10/125um

Environmental standards

Working Environment	Operating temperature: -10~50°C
	Storage temperature: -40~70°C
	Operating Humidity: 10%~90%, No condensation
	Storage Humidity: 5%~90%, No condensation



Function indication

PWR(Power indicator)	Lighting: Powered , Un-Light: No Power
SYS(System lights)	Lighting: System is normal , Flashing: system startup
Link(Link light)	Lighting: Connecting , Un-Light: Disconnect
Act(data light)	Flashing: Data Transmit , Un-Light: Disconnect

Physical specifications

Product Information	Product Dimensions: 440*205*44mm
	Package Dimensions: 500*290*85mm
	Product N.W: 2.53KG
	Product G.W: 3.14KG
Packing Information	Carton Dimensions: 520*445*300mm
	Packing Qantity: 5 PCS
	Packing weight: 16.7KG
Voltage	Input Voltage: AC100-240V/50-60Hz
	Power supply: 12V3A

Software function

Basic function	Support hardware watchdog, factory reset, system and port LED
	Support global information, statistical information, log information
	Support User management, alarm management, configuration management
	Support Port rate, duplex, flow control, maximum frame length configuration
Layer 3 Interface	Support Port mirroring, port speed limit, port energy saving
	Support Layer 3 interface
	Support IPv4, IPv6 address configuration
	Support ARP configuration
Layer 3 Routing	Support ND configuration
	Support IPv4 static routing
	Support IPv6 static routing
	Support RIP V1/V2
DHCP	Support OSPF
	Support DHCP server
	Support DHCP relay
	Support DHCP Snooping



VLAN	Support 4K VLAN
	Support 802.1Q VLAN, based on port VLAN
	Support Access, Trunk, Hybrid VLAN mode
	Support GVRP (VLAN registration protocol)
	Support MAC VLAN, IP VLAN
	Support Voice VLAN
MAC Address	Support MAC address automatic learning and aging
	Support Static, dynamic, filtered address table
Security features	Password protection
	Support Restrict user access based on port number, IP address, MAC address
	Support HTTPS, SSH V1/V2
	Support IP-MAC-PORT-VLAN binding
	Support ARP detection, IP source protection, DoS protection
	Support DHCP Snooping, DHCP Attack protection
	Support 802.1X Certification
	Support AAA (Authentication, Authorization, Accounting), Support RADIUS protocol, TACACS+
	Support Port security, port isolation

Access control	Support L2(Layer 2)~L4(Layer 4) Packet filtering function
	Support Port mirroring, flow rate limiting, QoS remarking
QOS	Support 8 port queues
	Support Port priority, 802.1P priority, DSCP priority
	Support SP, WRR Priority scheduling algorithm
Spanning tree	Support STP(IEEE 802.1d), RSTP(IEEE 802.1w) and MSTP(IEEE 802.1s) protocol
	Support Multi-instance, Support Aggregate interface
	Support BPDU protection
Multicast	Support IGMP v1/v2/v3 Snooping
	Support MLD v1/v2 Snooping
	Support Layer 2 multicast fast leave mechanism, querier
	Support Layer 2 IPv4 static multicast
	Support Layer 2 IPv6 static multicast
	Support IGMP v1/v2/v3 Layer 3 multicast
Storm suppression	Support multicast suppression
	Support broadcast storm suppression
	Support unknown unicast suppression
Ring protection	Support Ring protection



Link Aggregation	Support Static Aggregation
	Support LACP Dynamic Aggregation
	Support based on IP, MAC, mixed load-balancing modes
	Maximum support 32 aggregation groups (8 ports per aggregation group)
IPv6	Support IPv6 Ping、 IPv6 Traceroute、 IPv6 Telnet
	Support IPv6 SSH
	Support IPv6 HTTP 、 IPv6 HTTPS
Management and Maintenance	Support WEB Management (HTTP、 HTTPS)
	Support CLI (Telnet, SSH V1/V2, Local serial port)
	Support SNMP V1/V2/V3
	Support RMON V2
	Support LLDP Device discovery
	Support SNTP Time synchronization
	Support CPU Monitoring, Memory Monitoring
	Support System log, classification warning
Support Ping, Traceroute detection, cable detection	